



Dimensions 70C18

A Wheelbase	3450	3750	4350	4750
B Overall length	5905	6505	7340	8200
C Front overhang	998	998	998	998
D Rear overhang	1355	1665	1885	2350
E Maximum cab width	2060	2060	2060	2060
F Front axle to back of cab	1355	1355	1355	1355
H Front axle to body	1410	1410	1410	1410
Cab gap	55	55	55	55
K Overall height (unladen)	2335	2330	2325	2320
L Frame height at rear	850	850	850	850
with opt. rear air susp - raised	720+85	720+85	720+85	720+85
with opt. rear air susp - lowered	720-65	720-65	720-65	720-65
Turning circle (k to k) (m)	12.2	13.2	15.0	16.2
Turning circle (w to w) (m)	13.3	14.3	16.1	17.4

Body Dimensions

Maximum body width	2350	2350	2350	2350
Recommended max body length	3750	4350	5335	6200

Weights (kg)

Kerb weights are with full fuel tank, oil, water, spare wheel, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.

Model	70C18	70C18	70C18	70C18
Wheelbase	3450	3750	4350	4750
GVW	7000	7000	70000	7000
GTW	10500	10500	10500	10500
Kerb weights				
Front axle	1460	1470	1505	1505
Rear axle	825	830	830	860
Total	2285	2300	2335	2365
Maximum body & payload	4715	4700	4665	4635
Plated weights				
Front axle	2500	2500	2500	2500
Rear axle	5350	5350	5350	5350

Engines	C18
Fuel	Diesel
Capacity (litres)	3.0
Cylinders	4 (16 valves)
Emission Compliance	Euro 4
Fuel System	Common rail Generation 2
Power (hp/ kW)	176/ 130
@ rpm	3200-3500
Torque (Nm/ lbft)	400/ 295
@ rpm	1250-3000
Exhaust system	Centre emit
Exhaust with CRT	Standard

Gearboxes	C18
Type	6S400OD
	6 speed
	Synchromesh
	Overdrive
1st gear	5.37 : 1
Top gear	0.79 : 1

Performance		1st	Top
Gear		13	87
Max. geared speed (mph) (90kph limiter std.)		39	5
Gradeability @ GVW (%)			

Rear Axle Ratios	
Standard	4.30

Clutch	C18
Type	Hydraulic
Diameter	280

Electrics	
Alternator - std	14v - 110A
Alternator - opt	14v - 140A or 180A
Battery	12v - 110Ah

Lighting & Signalling
Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

Suspension	
Front	Independent with torsion bars
Rear	Semi-elliptic leaf spring
Anti-roll Bar	Front and rear
Shock absorbers	Front and rear

Brakes	
Front / diameter	Ventilated disc brakes / 301 mm
Rear / diameter	Ventilated disc brakes / 306 mm
ESP 8	Standard
<i>(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)</i>	
Parking brake	On rear axle

Steering	
	Power assisted - Rack & Pinion

Wheels & Tyres	
Wheels	6JK 16
Tyres	225/75R16
Spare	Standard

Fuel Tank	
	100 litres on nearside with locking fuel cap

Standard Equipment

Cab

Drivers airbag with seat belt pretensioners
Dual passenger seat with headrests
Fully adjustable driver's seat with headrest
Large dual storage pockets in doors
Three point inertia reel belt on all seats
Single piece floor mat
Windows electrically operated
Exterior mirrors with integrated wide angle and direction indicators
2 cup holders
Undersat storage
Bottle holder
Glove compartment with added storage
A4 storage compartment
Additional in-dash storage
Cooled compartment (with opt. air conditioning)
Clip holder

Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation
Windshield and side window defrost facility
Fresh air ventilation when heater turned off

Dashboard incorporates

Dash-mounted gear lever
RDS stereo radio/CD player (with Can security)
Provision for GPS or tachograph
Coolant temperature indicator
Tachograph - digital
Rev.counter
3 DIN drawers, two of which carry CD Player and/or tachograph
Comfort LCD Display Panel includes: odometer, trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

Security

Central locking with remote control and door locking management - anti-theft system
Engine immobiliser
Steering lock

Chassis

Flat topped high tensile steel c-section frame complete with pedestal body mounting brackets
Rear underslung spare wheel and carrier
Rear under ride guard

Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full catheporetic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Options

AGile automated 6-speed gearbox (10000kgs GTW)
Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)
Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags
Air conditioning
Alarm system
Alternator- heavy duty 180A
Ambient air temperature gauge (option with air conditioning)
Blue Tooth vivavoice system with steering wheel controls - Blue & me
Body builder connectors
Colour keyed bumper and trim
Comfort dashboard (Standard with CRT) - LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.
ECAS air suspension on rear axle
Exterior mirrors - heated and electrically adjustable
GPS satellite navigation
Headlamp washers
Long external mirror arm (Standard on 60C, 65C & 70C models)
Overhead windscreen storage rack and DIN drawer
PVC trim
Rear axle ratio options

Tow bar with ball
Towing electric socket (13 pin)

For a complete list of Daily options please contact your local Iveco distributor

DAILY

**70C18
CHASSIS CAB**

IVECO