



Dimensions 35C14/17

	SWB	MWB	LWB	XLWB
A Wheelbase	3000	3450	3750	4100
B Overall length	5334	5899	6509	6909
C Front overhang	998	998	998	998
D Rear overhang	1240	1355	1665	1715
E Maximum cab width	1996	1996	1996	1996
F Front axle to back of cab	1355	1355	1355	1355
H Front axle to body	1410	1410	1410	1410
Cab gap	55	55	55	55
K Overall height (unladen)	2230	2220	2215	2210
L Frame height at rear	755	755	755	755
with opt. rear air susp - raised	650+70	650+70	650+70	650+70
with opt. rear air susp - lowered	650-50	650-50	650-50	650-50
Turning circle (k to k) (m)	10.3	11.7	12.5	13.5
Turning circle (w to w) (m)	11.5	12.8	13.7	14.7

Body Dimensions

Maximum body width	2200	2200	2200	2200
Option	2350	2350	2350	2350
Recommended max body length	3315	3880	4490	4890

Weights (kg)

Kerb weights are with full fuel tank, oil, water, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.

Model	35C14/17			
Wheelbase	3000	3450	3750	4100
GVW	3500	3500	3500	3500
GTW	7000	7000	7000	7000
Kerb weights				
Front axle	1285	1315	1320	1335
Rear axle	590	580	585	580
Total	1870	1895	1905	1915
Maximum body & payload	1630	1605	1595	1585
Plated weights				
Front axle	1800	1800	1800	1800
Rear axle	2600	2600	2600	2600

Engines	C14	C17
Fuel	Diesel	Diesel
Capacity (litres)	3.0	3.0
Cylinders	4 (16 valves)	
Emission Compliance	EEV	
Fuel System	Common rail Generation 2	
Power (hp/ kW)	140/ 103	170/ 125
@ rpm	2800-3500	2990-3500
Torque (Nm/ lbft)	350/ 258	400/ 295
@ rpm	1250-2800	1250-2990
Exhaust system	Side emit - RHS	
Exhaust with CRT	Standard	

Gearboxes	C14	C17
Type	6S400OD	6S400OD
	6 speed	6 speed
	Synchromesh	
	Overdrive	
1st gear	5.37 : 1	5.37 : 1
Top gear	0.79 : 1	0.79 : 1

Performance for HR Models

Gear	1st	Top	1st	Top
Max. geared speed (mph)	12	85	14	92
Gradeability @ GVW (%)	40+	9	40+	9

Rear Axle Ratios

Standard	3.91	3.60
----------	------	------

Clutch	C14	C17
Type	Hydraulic	Hydraulic
Diameter	280	280

Electrics

Alternator - std	14v - 110A
Alternator - opt	14v - 140A or 180A
Battery	12v - 110Ah
13 pin towing electrics	

Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

Suspension

Front	Independent with transverse leaf spring
Rear	Parabolic leaf spring
Anti-roll Bar	Front and rear
Shock absorbers	Front and rear

Brakes

Front / diameter	Ventilated disc brakes / 290 mm
Rear / diameter	Ventilated disc brakes / 290 mm
ESP 8	Standard
(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)	
Parking brake	On rear axle

Steering

Power assisted - Rack & Pinion

Wheels & Tyres

Wheels	6JK 16
Tyres	195/65R16
Spare	Option

Fuel Tank

70 litres on nearside with locking fuel cap

Standard Equipment

Cab

Drivers airbag with seat belt pretensioners
Dual passenger seat with headrests
Fully adjustable driver's seat with headrest
Large dual storage pockets in doors
Three point inertia reel belt on all seats
Single piece floor mat
Windows electrically operated
Exterior mirrors with integrated wide angle and direction indicators
2 cup holders
Underseat storage
Bottle holder
Glove compartment with added storage
A4 storage compartment
Additional in-dash storage
Cooled compartment (with opt. air conditioning)
Clip holder

Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation
Windshield and side window defrost facility
Fresh air ventilation when heater turned off

Dashboard incorporates

Dash-mounted gear lever
RDS stereo radio/CD player (with Can security)
Provision for GPS or tachograph
Coolant temperature indicator
Speedometer
Rev.counter
3 DIN drawers, two of which carry CD Player and/or tachograph
Comfort LCD Display Panel
(See description under Options)

Security

Central locking with remote control and door locking management - anti-theft system
Engine immobiliser
Steering lock

Chassis

Flat topped high tensile steel c-section frame complete with pedestal body mounting brackets
Rear underslung spare wheel and carrier
Rear under ride guard

Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full catheporetic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Options

AGile automated 6-speed gearbox
Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)
Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags
Air conditioning
Alarm system
Alternator- heavy duty 180A
Ambient air temperature gauge (option with air conditioning)
Blue Tooth vivavoice system with steering wheel controls - Blue & me
Body builder connectors
Colour keyed bumper and trim
Comfort dashboard (Standard with CRT) - LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.
ECAS air suspension on rear axle
Exterior mirrors - heated and electrically adjustable
Fuel tank with locking cap - 100 litres
GPS satellite navigation
Headlamp washers
Long external mirror arm (Standard on 60C & 65C models)
Overhead windscreen storage rack and DIN drawer
PVC trim
Rear axle ratio options
Spare wheel
Tachograph - digital
Tow bar with ball

For a complete list of Daily options please contact your local Iveco distributor

ECODAILY 35C14/I7EEV
CHASSIS CAB

IVECO