



Dimensions

60C17 XHR

A Wheelbase	3950
Roof	XHR
B Overall length	7012
C Front overhang	998
D Rear overhang	2064
E Overall width	2174
K Overall height (unladen)	3025
S Rear loading height	870
with opt rear air susp - raised	800+85
with opt rear air susp - lowered	800-65
Turning circle (k to k) (m)	13.8
Turning circle (w to w) (m)	14.9

Cargo Area

Capacity (m ³)	17.2
Internal length	4560
Internal width	1800
Internal height	2100
Width between wheelarches	1030

Load Access

Rear door opening width	1540
Rear door opening height	1990
Rear door opening angle (deg)	270
Side door opening width	1250
Side opening height	1780

Weights (kg)

Kerb weights are with full fuel tank, oil, water, spare wheel, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.

Wheelbase	3950
GVW	6000
GTW	9500
Kerb weights	
Front axle	1475
Rear axle	1360
Total	2835
Maximum Payload	3165
Plated weights	
Front axle	2300
Rear axle	4650

Engines		C17
Fuel		Diesel
Capacity (litres)		3.0
Cylinders		4 (16 valves)
Emission Compliance		EEV
Fuel System		Common rail Generation 2
Power (hp/ kW)		170/ 125
@ rpm		3050-3600
Torque (Nm/ lbft)		400/ 295
@ rpm		1250-2990
Exhaust system		Side emit - RHS
Exhaust with CRT		Standard
Gearboxes		C17
Type		6S400OD
		6 speed
		Synchromesh
		Overdrive
1st gear		5.37 : 1
Top gear		0.79 : 1
Performance		
Gear	1st	Top
Max. geared speed (mph) (90kph limiter std.)	13	88
Gradeability @ GVW (%)	40+	6
Rear Axle Ratios		
Std. with XHR		4.33
Clutch		C17
Type		Hydraulic
Diameter		280

Standard Equipment

Cab

Drivers airbag with seat belt pretensioners
Dual passenger seat with headrests
Fully adjustable driver's seat with headrest
Large dual storage pockets in doors
Three point inertia reel belt on all seats
Single piece floor mat
Windows electrically operated
Exterior mirrors with integrated wide angle and direction indicators
2 cup holders
Underseat storage
Bottle holder
Glove compartment with added storage
A4 storage compartment
Additional in-dash storage
Cooled compartment (with opt. air conditioning)
Clip holder

Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation
Windshield and side window defrost facility
Fresh air ventilation when heater turned off

Dashboard incorporates

Dash-mounted gear lever
RDS stereo radio/CD player (with Can security)
Provision for GPS or tachograph
Coolant temperature indicator
Tachograph - digital
Rev. counter
3 DIN drawers, two of which carry CD Player and/or tachograph
Comfort LCD Display Panel includes: odometer, trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

Security

Central locking with remote control and door locking management - anti-theft system
Engine immobiliser
Unglazed full bulkhead
Unglazed rear doors
Steering lock

Load Area

Floor - steel ribbed with load lashing rings
Sides - reinforced with load lashing rings
Side access via top hung side sliding door with internal step and grab handle
Rear access by hinged doors with steps at 90 and 270 degrees and grab handle
Interior lights at side and rear (door operated with individual isolation)

Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full catheporetic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Electrics

Alternator - std 14v - 110A
Alternator - opt 14v - 140A or 180A
Battery 12v - 110Ah

Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

Suspension

Front Independent with torsion bars
Rear Parabolic leaf spring
Anti-roll Bar Front and rear
Shock absorbers Front and rear

Brakes

Front / diameter Ventilated disc brakes / 301 mm
Rear / diameter Ventilated disc brakes / 306 mm
ESP 8 Standard
(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)
Parking brake On rear axle

Steering

Power assisted - Rack & Pinion

Wheels & Tyres

Wheels 6JK 16
Tyres 225/75R16
Spare Located behind left wheel arch in rear

Fuel Tank

100 litres on nearside with locking fuel cap

Options

AGile automated 6-speed gearbox
Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)
Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags
Air conditioning
Alarm system to cab and load area
Alternator- heavy duty 180A
Ambient air temperature gauge (option with air conditioning)
Blue Tooth vivavoice system with steering wheel controls - Blue & me
Body builder connectors
Colour keyed bumper and trim
Comfort dashboard (Standard with CRT)
- LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.
ECAS air suspension on rear axle
Exterior mirrors - heated and electrically adjustable
GPS satellite navigation
Headlamp washers
Overhead windscreen storage rack and DIN drawer
PVC trim
Rear axle ratio options
Rear camera and spot light
Reverse parking sensor integrated into rear step
Third stop light
Tow bar with ball
Towing electric socket (13 pin)

For a complete list of Daily options please contact your local Iveco distributor

ECODAILY

**60C17EEV
VAN**

IVECO