



Dimensions 35S11/13/14/18

| | | | | | | | | |
|------------------------------------|--------|--------|--------|--------|--------|--------|--------|--------|
| A Wheelbase | 3000 | 3000L | 3000 | 3000L | 3300 | 3950 | 3300 | 3950 |
| Roof | LR | LR | HR | HR | HR | HR | XHR | XHR |
| B Overall length | 5077 | 5477 | 5077 | 5477 | 5997 | 7012 | 5997 | 7012 |
| C Front overhang | 998 | 998 | 998 | 998 | 998 | 998 | 998 | 998 |
| D Rear overhang | 1079 | 1479 | 1079 | 1479 | 1699 | 2064 | 1699 | 2064 |
| E Overall width | 1996 | 1996 | 1996 | 1996 | 1996 | 1996 | 1996 | 1996 |
| K Overall height (unladen) | 2270 | 2270 | 2645 | 2645 | 2640 | 2670 | 2825 | 2869 |
| S Rear loading height | 695 | 695 | 695 | 695 | 695 | 695 | 695 | 695 |
| with opt. rear air susp. - raised | 645+40 | 645+40 | 645+40 | 645+40 | 645+40 | 645+40 | 645+40 | 645+40 |
| with opt. rear air susp. - lowered | 645-60 | 645-60 | 645-60 | 645-60 | 645-60 | 645-60 | 645-60 | 645-60 |
| Turning circle (k to k) (m) | 10.4 | 10.4 | 10.4 | 10.4 | 11.2 | 13.1 | 11.2 | 13.1 |
| Turning circle (w to w) (m) | 11.5 | 11.5 | 11.5 | 11.5 | 12.4 | 14.3 | 12.4 | 14.3 |

Cargo Area

| | | | | | | | | |
|---------------------------|------|------|------|------|------|------|------|------|
| Capacity (m³) | 7.3 | 8.3 | 9.0 | 10.2 | 12.0 | 15.6 | 13.2 | 17.2 |
| Internal length | 2600 | 3000 | 2600 | 3000 | 3520 | 4560 | 3520 | 4560 |
| Internal width | 1800 | 1800 | 1800 | 1800 | 1800 | 1800 | 1800 | 1800 |
| Internal height | 1545 | 1545 | 1900 | 1900 | 1900 | 1900 | 2100 | 2100 |
| Width between wheelarches | 1320 | 1320 | 1320 | 1320 | 1320 | 1320 | 1320 | 1320 |

Load Access

| | | | | | | | | |
|-------------------------------|------|------|------|------|------|------|------|------|
| Rear door opening width | 1540 | 1540 | 1540 | 1540 | 1540 | 1540 | 1540 | 1540 |
| Rear door opening height | 1430 | 1430 | 1780 | 1780 | 1780 | 1780 | 1990 | 1990 |
| Rear door opening angle (deg) | 180 | 270 | 180 | 270 | 270 | 270 | 270 | 270 |
| Side door opening width | 1100 | 1100 | 1100 | 1100 | 1250 | 1250 | 1250 | 1250 |
| Side opening height | 1415 | 1415 | 1780 | 1780 | 1780 | 1780 | 1780 | 1780 |

Weights (kg)

Kerb weights are with full fuel tank, oil, water, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.

| | 35S11/13/14 | | 35S11/13/14 | | | | 35S11/13/14 | |
|----------------------------------|-------------|-------|-------------|-------|------|------|-------------|------|
| Wheelbase | 3000 | 3000L | 3000 | 3000L | 3300 | 3950 | 3300 | 3950 |
| GVW | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 |
| GTW | 6300 | 6300 | 6300 | 6300 | 6300 | 6300 | 6300 | 6300 |
| Kerb weights* (see below) | | | | | | | | |
| Front axle | 1240 | 1210 | 1215 | 1210 | 1230 | 1275 | 1225 | 1275 |
| Rear axle | 740 | 810 | 775 | 850 | 905 | 985 | 935 | 1020 |
| Total | 1980 | 2020 | 1990 | 2060 | 2135 | 2260 | 2160 | 2295 |
| Maximum Payload | 1520 | 1480 | 1510 | 1440 | 1365 | 1240 | 1340 | 1205 |
| Plated weights | | | | | | | | |
| Front axle | 1800 | 1800 | 1800 | 1800 | 1800 | 1800 | 1800 | 1800 |
| Rear axle | 2240 | 2240 | 2240 | 2240 | 2240 | 2240 | 2240 | 2240 |

* For 35S18 Models add 25kgs on the front axle and 10kgs on the rear axle

| Engines | S11 | S13 | S14 | S18 |
|---------------------|---|----------|----------|----------|
| Fuel | Diesel | Diesel | Diesel | Diesel |
| Capacity (litres) | 2.3 | 2.3 | 2.3 | 3.0 |
| Cylinders | 4 (16 valves) | | | |
| Emission Compliance | Euro 4 | | | |
| Fuel System | Common rail Generation 2 | | | |
| Power (hp/ kW) | 106/ 78 | 126/ 93 | 136/ 100 | 176/ 130 |
| @ rpm | 2750-3900 3050-3600 3000-3900 3200-3500 | | | |
| Torque (Nm/ lbft) | 270/ 199 | 290/ 213 | 320/ 236 | 400/ 295 |
| @ rpm | 1800-2750 1650-3050 1700-3000 1250-3000 | | | |
| Exhaust system | Side emit - RHS | | | |

| Gearboxes | S11 | S13 | S14 | S18 |
|-----------|--------------|----------|----------|----------|
| Type | 5S300OD | 5S300OD | 5S300OD | 6S400OD |
| | 5 speed | 5 speed | 5 speed | 6 speed |
| | Synchronmesh | | | |
| | Overdrive | | | |
| 1st gear | 4.99 : 1 | 4.99 : 1 | 4.99 : 1 | 5.37 : 1 |
| Top gear | 0.78 : 1 | 0.78 : 1 | 0.78 : 1 | 0.79 : 1 |

Performance for HR Models

| Gear | Ist | Top | Ist | Top | Ist | Top | Ist | Top |
|-------------------------|-----|-----|-----|-----|-----|-----|-----|-----|
| Max. geared speed (mph) | 16 | 100 | 15 | 93 | 17 | 106 | 16 | 112 |
| Gradeability @ GVW (%) | 40+ | 6 | 40+ | 7 | 40+ | 7 | 40+ | 8 |

Rear Axle Ratios

| | | | | |
|--------------------|------|------|------|------|
| Std. with LR | 3.60 | 3.60 | 3.73 | 3.15 |
| Std. with HR & XHR | 3.91 | 3.91 | 3.73 | 3.15 |

| Clutch | S11 | S13 | S14 | S18 |
|----------|-----------|-----------|-----------|-----------|
| Type | Hydraulic | Hydraulic | Hydraulic | Hydraulic |
| Diameter | 267 | 267 | 267 | 280 |

Electrics

| | |
|--|--------------------|
| Alternator - std | 14v - 110A |
| Alternator - opt | 14v - 140A or 180A |
| Battery | 12v - 110Ah |
| 13 pin towing electrics (.13/.14/.18 engines only) | |

Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

Suspension

| | |
|-----------------|---|
| Front | Independent with transverse leaf spring |
| Rear | Single leaf parabolic |
| Anti-roll Bar | Standard on rear |
| Shock absorbers | Front and rear |

Brakes

| | |
|---|---------------------------------|
| Front / diameter | Ventilated disc brakes / 300 mm |
| Rear / diameter | Disc brakes / 296 mm |
| ESP 8 | Standard |
| <i>(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)</i> | |
| Parking brake | On rear axle |

Steering

Power assisted - Rack & Pinion

Wheels & Tyres

| | |
|--------|-----------|
| Wheels | 6JK 16 |
| Tyres | 225/65R16 |
| Spare | Option |

Fuel Tank

70 litres on nearside with locking fuel cap

Standard Equipment

Cab

Drivers airbag with seat belt pretensioners
Dual passenger seat with headrests
Fully adjustable driver's seat with headrest
Large dual storage pockets in doors
Three point inertia reel belt on all seats
Single piece floor mat
Windows electrically operated
Exterior mirrors with integrated wide angle and direction indicators
2 cup holders
Underseat storage
Bottle holder
Glove compartment with added storage
A4 storage compartment
Additional in-dash storage
Cooled compartment (with opt. air conditioning)
Clip holder

Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation
Windshield and side window defrost facility
Fresh air ventilation when heater turned off

Dashboard incorporates

Dash-mounted gear lever
RDS stereo radio/CD player (with Can security)
Provision for GPS or tachograph
Coolant temperature indicator
Speedometer
Rev. counter
3 DIN drawers, two of which carry CD Player and/or tachograph
LCD Display Panel includes: odometer, trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

Security

Central locking with remote control and door locking management - anti-theft system
Engine immobiliser
Unglazed full bulkhead
Unglazed rear doors
Steering lock

Load Area

Floor - steel ribbed with load lashing rings
Sides - reinforced with load lashing rings
Side access via top hung side sliding door with internal step and grab handle
Rear access by hinged doors with stops at 90 and 270 degrees (90 and 180 degrees on 3000 wheelbase) and grab handle
Interior lights at side and rear (door operated with individual isolation)

Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full catheporetic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Options

AGile automated 6-speed gearbox
Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)
Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags
Air conditioning
Alarm system to cab and load area
Alternator- heavy duty 180A
Ambient air temperature gauge (option with air conditioning)
Blue Tooth vivavoice system with steering wheel controls - Blue & me
Body builder connectors
Colour keyed bumper and trim
Comfort dashboard (Standard with CRT) - LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.
ECAS air suspension on rear axle
Exhaust with particulate trap (CRT)
Exterior mirrors - heated and electrically adjustable
Fuel tank with locking cap - 100 litres
GPS satellite navigation
Headlamp washers
Overhead windscreen storage rack and DIN drawer
PVC trim
Rear axle ratio options
Rear camera and spot light
Reverse parking sensor integrated into rear step
Spare wheel

Tachograph - digital
Third stop light
Tow bar with ball
Towing electric socket (13 pin) (.11 engine only)

For a complete list of Daily options please contact your local Iveco distributor

DAILY

**35S11/13/14/18
VAN**

IVECO