



**Dimensions**                      **40C11/13**                      **40C15/18**

A Wheelbase	3450	3750	4100	3450	3750	4100
B Overall length	5899	6509	6909	5899	6509	6909
C Front overhang	998	998	998	998	998	998
D Rear overhang	1355	1665	1715	1355	1665	1715
E Maximum cab width	1996	1996	1996	1996	1996	1996
F Front axle to back of cab	2105	2105	2105	2105	2105	2105
H Front axle to body	2160	2160	2160	2160	2160	2160
Cab gap	55	55	55	55	55	55
K Overall height (unladen)	2290	2285	2280	2290	2285	2280
L Frame height at rear	735	735	735	735	735	735
with opt. rear air susp - raised	-	650+70	650+70	-	650+70	650+70
with opt. rear air susp - lowered	-	650-50	650-50	-	650-50	650-50
Turning circle (k to k) (m)	12.5	13.4	14.5	12.5	13.4	14.5
Turning circle (w to w) (m)	13.6	14.5	15.6	13.6	14.5	15.6

**Body Dimensions**

Maximum body width	2200	2200	2200	2200	2200	2200
Option	2350	2350	2350	2350	2350	2350
Recommended max body length	3135	3745	4155	3135	3745	4155

**Weights (kg)**

Kerb weights are with full fuel tank, oil, water, spare wheel, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.

Model	40C11/13			40C15/18		
Wheelbase	3450	3750	4100	3450	3750	4100
GVW	4200	4200	4200	4200	4200	4200
GTW	7700	7700	7700	7700	7700	7700
<b>Kerb weights</b>						
Front axle	1450	1450	1495	1490	1495	1540
Rear axle	740	750	715	720	725	695
Total	2190	2200	2210	2210	2220	2235
Maximum body & payload	2010	2000	1990	1990	1980	1965
<b>Plated weights</b>						
Front axle	1900	1900	1900	1900	1900	1900
Rear axle	3100	3100	3100	3100	3100	3100

Engines	C11	C13	C15	C18
Fuel	Diesel	Diesel	Diesel	Diesel
Capacity (litres)	2.3	2.3	3.0	3.0
Cylinders	4 (16 valves)			
Emission Compliance	Euro 4			
Fuel System	Common rail Generation 2			
Power (hp/ kW)	106/ 78	126/ 93	146/ 107	176/ 130
@ rpm	2750-3900 3050-3600 3000-3500 3200-3500			
Torque (Nm/ lbft)	270/ 199	290/ 213	350/ 258	400/ 295
@ rpm	1800-2750 1650-3050 1400-2600 1250-3000			
Exhaust system	Side emit - RHS			

Gearboxes	C11	C13	C15	C18
Type	5S300OD	5S300OD	6S400OD	6S400OD
	5 speed	5 speed	6 speed	6 speed
	Synchronmesh			
	Overdrive			
1st gear	4.99 : 1	4.99 : 1	5.37 : 1	5.37 : 1
Top gear	0.78 : 1	0.78 : 1	0.79 : 1	0.79 : 1

#### Performance for HR Models

Gear	Ist	Top	Ist	Top	Ist	Top	Ist	Top
Max. geared speed (mph)	14	89	14	87	12	84	13	89
Gradeability @ GVW (%)	40+	6	40+	6	40+	8	40+	8

#### Rear Axle Ratios

Standard	4.44	4.18	4.18	3.91
----------	------	------	------	------

Clutch	C11	C13	C15	C18
Type	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Diameter	267	267	280	280

#### Electrics

Alternator - std	14v - 110A
Alternator - opt	14v - 140A or 180A
Battery	12v - 110Ah

#### Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

#### Suspension

Front	Independent with torsion bars
Rear	Semi-elliptic leaf spring
Anti-roll Bar	Front and rear
Shock absorbers	Front and rear

#### Brakes

Front / diameter	Ventilated disc brakes / 290 mm
Rear / diameter	Disc brakes / 289 mm
ESP 8	Standard
<i>(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)</i>	
Parking brake	On rear axle

#### Steering

Power assisted - Rack & Pinion

#### Wheels & Tyres

Wheels	6JK 16
Tyres	195/75R16
Spare	Standard

#### Fuel Tank

70 litres on nearside with locking fuel cap

## Standard Equipment

#### Cab (6+1)

Drivers airbag with seat belt pretensioners  
Dual passenger seat with headrests  
Fully adjustable driver's seat with headrest  
4 passenger rear seat with headrests  
Large dual storage pockets in doors  
Three point inertia reel belt on front seats and rear outer seats. Inertia lap belt for rear centre seats  
Single piece floor mat  
Windows electrically operated  
Exterior mirrors with integrated wide angle and direction indicators  
2 cup holders  
Undersat storage  
Bottle holder  
Glove compartment with added storage  
A4 storage compartment  
Additional in-dash storage  
Cooled compartment (with opt. air conditioning)  
Clip holder  
Rear panel with small window  
Rear door with sliding window  
Additional light in rear  
Support handle in rear for outer passengers

#### Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation  
Windshield and side window defrost facility  
Fresh air ventilation when heater turned off

#### Dashboard incorporates

Dash-mounted gear lever  
RDS stereo radio/CD player (with Can security)  
Provision for GPS or tachograph

#### Dashboard incorporates (cont'd)

Coolant temperature indicator  
Tachograph - digital  
Rev.counter  
3 DIN drawers, two of which carry CD Player and/or tachograph  
LCD Display Panel includes: odometer, trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

#### Security

Central locking with remote control and door locking management - anti-theft system  
Engine immobiliser  
Steering lock

#### Chassis

Flat topped high tensile steel c-section frame complete with pedestal body mounting brackets  
Rear underslung spare wheel and carrier  
Rear under ride guard

#### Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full cathoretic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

## Options

AGile automated 6-speed gearbox  
Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)  
Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags  
Air conditioning  
Alarm system  
Alternator- heavy duty 180A  
Ambient air temperature gauge (option with air conditioning)  
Blue Tooth vivavoice system with steering wheel controls - Blue & me  
Body builder connectors  
Colour keyed bumper and trim  
Comfort dashboard (Standard with CRT) - LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.  
ECAS air suspension on rear axle  
Exhaust with particulate trap (CRT)  
Exterior mirrors - heated and electrically adjustable  
Fuel tank with locking cap - 100 litres  
GPS satellite navigation  
Headlamp washers  
Long external mirror arm (Standard on 60C & 65C models)  
Overhead windscreen storage rack and DIN drawer  
PVC trim  
Rear axle ratio options  
Tow bar with ball  
Towing electric socket (13 pin)

*For a complete list of Daily options please contact your local Iveco distributor*

**DAILY**

**40C11/13/15/18  
CREW CAB**

**IVECO**