



Dimensions 45C15/18

A Wheelbase	3450	3750	4350
B Overall length	5928	6538	7358
C Front overhang	998	998	998
D Rear overhang	1355	1665	1885
E Maximum cab width	1996	1996	1996
F Front axle to back of cab	2105	2105	2105
H Front axle to body	2160	2160	2160
Cab gap	55	55	55
K Overall height (unladen)	2295	2290	2280
L Frame height at rear	750	750	750
Turning circle (k to k) (m)	12.5	13.4	15.3
Turning circle (w to w) (m)	13.6	14.5	16.4

Body Dimensions

Maximum body width	2200	2200	2200
Option	2350	2350	2350
Recommended max body length	2960	3650	4590

Weights (kg)

Kerb weights are with full fuel tank, oil, water, spare wheel, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.

Model	45C15/18	45C15/18	45C15/18
Wheelbase	3450	3750	4350
GVW	4600	4600	4600
GTW	8100	8100	8100
Kerb weights			
Front axle	1495	1515	1560
Rear axle	745	745	725
Total	2240	2260	2285
Maximum body & payload	2360	2340	2315
Plated weights			
Front axle	1900	1900	1900
Rear axle	3400	3400	3400

Engines	C15	C18
Fuel	Diesel	Diesel
Capacity (litres)	3.0	3.0
Cylinders	4 (16 valves)	
Emission Compliance	Euro 4	
Fuel System	Common rail	Generation 2
Power (hp/ kW)	146/ 107	176/ 130
@ rpm	3000-3500	3200-3500
Torque (Nm/ lbft)	350/ 258	400/ 295
@ rpm	1400-2600	1250-3000
Exhaust system	Centre emit	

Gearboxes	C15	C18
Type	6S400OD	6S400OD
	6 speed	6 speed
	Synchromesh	
	Overdrive	
1st gear	5.37:1	5.37:1
Top gear	0.79:1	0.79:1

Performance

Gear	1st	Top	1st	Top
Max. geared speed (mph) (90kph limiter std.)	12	84	13	89
Gradeability @ GVW (%)	40+	7	40+	7

Rear Axle Ratios

Standard	4.18	3.91
----------	------	------

Clutch	C15	C18
Type	Hydraulic	Hydraulic
Diameter	280	280

Electrics

Alternator - std	14v - 110A
Alternator - opt	14v - 140A or 180A
Battery	12v - 110Ah

Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

Suspension

Front	Independent with torsion bars
Rear	Semi-elliptic leaf spring
Anti-roll Bar	Front and rear
Shock absorbers	Front and rear

Brakes

Front / diameter	Ventilated disc brakes / 290 mm
Rear / diameter	Disc brakes / 289 mm
ESP 8	Standard
(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)	
Parking brake	On rear axle

Steering

Power assisted - Rack & Pinion

Wheels & Tyres

Wheels	6JK 16
Tyres	195/75R16
Spare	Standard

Fuel Tank

70 litres on nearside with locking fuel cap

Standard Equipment

Cab (6+1)

Drivers airbag with seat belt pretensioners
Dual passenger seat with headrests
Fully adjustable driver's seat with headrest
4 passenger rear seat with headrests
Large dual storage pockets in doors
Three point inertia reel belt on front seats and rear outer seats. Inertia lap belt for rear centre seats
Single piece floor mat
Windows electrically operated
Exterior mirrors with integrated wide angle and direction indicators
2 cup holders
Undersat storage
Bottle holder
Glove compartment with added storage
A4 storage compartment
Additional in-dash storage
Cooled compartment (with opt. air conditioning)
Clip holder
Rear panel with small window
Rear door with sliding window
Additional light in rear
Support handle in rear for outer passengers

Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation
Windshield and side window defrost facility
Fresh air ventilation when heater turned off

Dashboard incorporates

Dash-mounted gear lever
RDS stereo radio/CD player (with Can security)
Provision for GPS or tachograph

Dashboard incorporates (cont'd)

Coolant temperature indicator
Tachograph - digital
Rev.counter
3 DIN drawers, two of which carry CD Player and/or tachograph
LCD Display Panel includes: odometer, trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

Security

Central locking with remote control and door locking management - anti-theft system
Engine immobiliser
Steering lock

Chassis

Flat topped high tensile steel c-section frame complete with pedestal body mounting brackets
Rear underslung spare wheel and carrier
Rear under ride guard

Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full catheporetic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Options

AGile automated 6-speed gearbox
Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)
Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags
Air conditioning
Alarm system
Alternator- heavy duty 180A
Ambient air temperature gauge (option with air conditioning)
Blue Tooth vivavoice system with steering wheel controls - Blue & me
Body builder connectors
Colour keyed bumper and trim
Comfort dashboard (Standard with CRT) - LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.
ECAS air suspension on rear axle
Exhaust with with particulate trap (CRT)
Exterior mirrors - heated and electrically adjustable
Fuel tank with locking cap - 100 litres
GPS satellite navigation
Headlamp washers
Long external mirror arm (Standard on 60C & 65C models)
Overhead windscreen storage rack and DIN drawer
PVC trim
Rear axle ratio options
Tow bar with ball
Towing electric socket (13 pin)

For a complete list of Daily options please contact your local Iveco distributor

DAILY

**45C15/18
CREW CAB**

IVECO