



Dimensions 50C15/18

A Wheelbase	3450	3750	4350	4750
B Overall length	5928	6538	7358	8223
C Front overhang	998	998	998	998
D Rear overhang	1355	1665	1885	2350
E Maximum cab width	1996	1996	1996	1996
F Front axle to back of cab	1355	1355	1355	1355
H Front axle to body	1410	1410	1410	1410
Cab gap	55	55	55	55
K Overall height (unladen)	2280	2275	2265	2265
L Frame height at rear	765	765	765	765
with opt. rear air susp - raised	660+70	660+70	660+70	660+70
with opt. rear air susp - lowered	660-50	660-50	660-50	660-50
Turning circle (k to k) (m)	12.5	13.4	15.3	16.5
Turning circle (w to w) (m)	13.6	14.5	16.4	17.7

Body Dimensions

Maximum body width	2200	2200	2200	2200
Option	2350	2350	2350	2350
Recommended max body length	3750	4350	5335	6190

Weights (kg)

Kerb weights are with full fuel tank, oil, water, spare wheel, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.

Model	50C15/18	50C15/18	50C15/18	50C15/18
Wheelbase	3450	3750	4350	4750
GVW	5200	5200	5200	5200
GTW	8700	8700	8700	8700
Kerb weights				
Front axle	1380	1395	1430	1425
Rear axle	645	655	645	675
Total	2025	2050	2075	2100
Maximum body & payload	3175	3150	3125	3100
Plated weights				
Front axle	1900	1900	1900	1900
Rear axle	3700	3700	3700	3700

Engines	C15	C18
Fuel	Diesel	Diesel
Capacity (litres)	3.0	3.0
Cylinders	4 (16 valves)	
Emission Compliance	Euro 4	
Fuel System	Common rail	Generation 2
Power (hp/ kW)	146/ 107	176/ 130
@ rpm	3000-3500	3200-3500
Torque (Nm/ lbft)	350/ 258	400/ 295
@ rpm	1400-2600	1250-3000
Exhaust system	Centre emit	

Gearboxes	C15	C18
Type	6S400OD	6S400OD
	6 speed	6 speed
	Synchromesh	
	Overdrive	
1st gear	5.37:1	5.37 : 1
Top gear	0.79 : 1	0.79 : 1

Performance	C15	C18
Gear	1st Top	1st Top
Max. geared speed (mph) (90kph limiter std.)	12 84	13 89
Gradeability @ GVW (%)	40+ 6	40+ 7

Rear Axle Ratios	C15	C18
Standard	4.18	3.91

Clutch	C15	C18
Type	Hydraulic	Hydraulic
Diameter	280	280

Electrics	C15	C18
Alternator - std	14v - 110A	
Alternator - opt	14v - 140A or 180A	
Battery	12v - 110Ah	

Lighting & Signalling
Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

Suspension	C15	C18
Front		Independent with torsion bars
Rear		Semi-elliptic leaf spring
Anti-roll Bar		Front and rear
Shock absorbers		Front and rear

Brakes	C15	C18
Front / diameter		Ventilated disc brakes / 290 mm
Rear / diameter		Disc brakes / 289 mm
ESP 8		Standard
(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)		
Parking brake		On rear axle

Steering
Power assisted - Rack & Pinion

Wheels & Tyres	C15	C18
Wheels		6JK 16
Tyres		195/75R16
Spare		Standard

Fuel Tank
70 litres on nearside with locking fuel cap

Standard Equipment

Cab

Drivers airbag with seat belt pretensioners
Dual passenger seat with headrests
Fully adjustable driver's seat with headrest
Large dual storage pockets in doors
Three point inertia reel belt on all seats
Single piece floor mat
Windows electrically operated
Exterior mirrors with integrated wide angle and direction indicators
2 cup holders
Underseat storage
Bottle holder
Glove compartment with added storage
A4 storage compartment
Additional in-dash storage
Cooled compartment (with opt. air conditioning)
Clip holder

Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation
Windshield and side window defrost facility
Fresh air ventilation when heater turned off

Dashboard incorporates

Dash-mounted gear lever
RDS stereo radio/CD player (with Can security)
Provision for GPS or tachograph
Coolant temperature indicator
Tachograph - digital
Rev.counter
3 DIN drawers, two of which carry CD Player and/or tachograph
LCD Display Panel includes: odometer, trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

Security

Central locking with remote control and door locking management - anti-theft system
Engine immobiliser
Steering lock

Chassis

Flat topped high tensile steel c-section frame complete with pedestal body mounting brackets
Rear underslung spare wheel and carrier
Rear under ride guard

Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full catheporetic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Options

AGile automated 6-speed gearbox
Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)
Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags
Air conditioning
Alarm system
Alternator- heavy duty 180A
Ambient air temperature gauge (option with air conditioning)
Blue Tooth vivavoice system with steering wheel controls - Blue & me
Body builder connectors
Colour keyed bumper and trim
Comfort dashboard (Standard with CRT) - LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.
ECAS air suspension on rear axle
Exhaust with particulate trap (CRT)
Exterior mirrors - heated and electrically adjustable
Fuel tank with locking cap - 100 litres
GPS satellite navigation
Headlamp washers
Long external mirror arm (Standard on 60C & 65C models)
Overhead windscreen storage rack and DIN drawer
PVC trim
Rear axle ratio options
Tow bar with ball

Towing electric socket (13 pin)

For a complete list of Daily options please contact your local Iveco distributor

DAILY

**50C15/18
CHASSIS CAB**

IVECO